



NANDHA ENGINEERING COLLEGE (Autonomous)

Affiliated to Anna University Chennai ✦ Approved by AICTE ✦ Accredited by NBA - New Delhi

Pitchandampalayam (P.O), Vaikkalmedu, Erode - Perundurai Road, Erode - 638 052

Phone : 04294 - 225585, 223711, 223722, 226393 Mobile : 73737 23722 Fax : 04294 - 224787

Website : www.nandhaengg.org

E.mail : info@nandhaengg.org

TENDER NOTICE

Tender No: NEC/AICTE/IDEA LAB/2025-26/01

Date: 25.08.2025


Nandha Engineering College hereby invites tenders through a two-bid system (technical and commercial) from qualified and reliable suppliers and vendors for the supply and installation of machinery and equipment with 3 year warranty for the **Establishment of a AICTE IDEA (Idea Development, Evaluation & Application) LAB at Nandha Engineering College, Vaikkalmedu, Erode.**

Prospective suppliers and vendors are requested to download the tender documents from our official website <https://nandhaengg.org/>- Completed tenders, along with the requisite credentials must be submitted in hard copy format, enclosed in a sealed cover to The Principal, Nandha Engineering College, Vaikkalmedu, Erode – 638052, Tamil Nadu, on or before 22nd September 2025, by 5:00 pm.




Chief Mentor

AICTE IDEA LAB
Dr. U.S. Ragupathy
Principal
Nandha Engineering College
(Autonomous)
Erode - 638 052, Tamil Nadu


25/8/25


25/8/25

Sr. No	Equipments	Specifications	Qty
1	Single Nozzle 3D printer	<p>Printing Technology: Fused Filament Fabrication (FFF) or Fused Deposition Modeling (FDM).</p> <p>Printable Area: The minimum printable area should be at least 390 x 390 x 390 mm or above</p> <p>Printer Design: Core XY or Cartesian. Temperature Range: Hot end: Up to 300°C or above Heat bed: Up to 120°C. or above.</p> <p>Nozzle: Compatible with All polymers, 0.4, 0.6 and 0.8mm</p> <p>Steel Sheet: Provided with satin or smooth PEI surface.</p> <p>Filament Diameter: 1.75mm (supports PLA, PETG, ASA, ABS, etc.).</p> <p>Extruder: Gearbox with 1/10 ratio, Speed : 550 MM/Sec or above</p> <p>Stepper Drivers for smooth motion. or equivalent</p> <p>Stepper Motors: Choose between 1.8° or precise 0.9° X, Y stepper motors.</p> <p>LCD Screen: 3.5" graphic 65k color screen or larger.</p> <p>Connectivity: USB drive, LAN, or internet. Supported Materials: PLA, PETG, ASA, ABS, PP, PC, flexible filaments, and more.</p> <p>Wi-Fi Module: Built-in (network connectivity not required for setup or operation).</p> <p>Compatibility: Windows, macOS, Linux.</p> <p>Printer Dimensions: The maximum physical dimensions of the system 700 X 700 X 700 or above. Fully enclosed Machine.</p>	1
2	SLA 3D printer	<p>Build Volume: 277.85 × 156.26 × 300 mm</p> <p>Printing Technology: SLA</p> <p>12.8-inch 6K monochrome LCD (5448 × 3064 pixels)</p> <p>XY resolution: 51 μm</p> <p>Layer Thickness: 0.01–0.2 mm</p> <p>Max Printing Speed: ~70 mm/h</p> <p>Z-Axis Accuracy: 0.02 mm, with a dual linear guide rail</p> <p>Light Source: COB (Chip-on-Board) + refractive lens, 405 nm wavelength</p> <p>Cooling: Fans and copper heat-sink tubes for efficient temperature control</p> <p>Auto Resin Management: Automatic resin feeding + recycling system, capped with special bottle-cap modules</p> <p>Build Plate: Laser-engraved surface with a 4-point leveling system and a rotatable handle for quick adjustments</p> <p>Display & Connectivity: 3.5-inch resistive touch screen for control USB (offline printing)</p>	

Sr. No	Equipments	Specifications	Qty
3	Dual Nozzle 3D printer	<p>Technology-FDM Build VolumeUp to 325 × 320 × 325 mm (single nozzle) ConstructionMetal + glass, compact frame ToolheadAll-metal, high-temp nozzle; supports 0.2–0.8 mm SpeedUp to 1000 mm/s; 40–65 mm³/s flow Temperature ControlHeated bed (120 °C), chamber (65 °C) Air FiltrationMulti-stage filters, closed-loop cooling Filament HandlingAMS 2 Pro with sensors and drying Sensors & CamerasFull monitoring and safety features UI & ControlTouchscreen, apps, AI-powered ConnectivityDual-band Wi-Fi (Ethernet optional in Pro) PowerDual-voltage support with robust wattage SoftwareBambu ecosystem + slicer compatibility</p>	1
4	SLS 3D printer	<p>TechnologySLS (Polymer Powder Bed Fusion) MaterialNylon PA-12 Build Volume150 × 150 × 150 mm Laser5 W diode laser Layer Thickness0.1–0.3 mm Build Accuracy± 0.2 mm Wall Thickness (min)0.5 mm Power Requirements240 V/50 Hz, 1.5 kW avg / 2.5 kW peak Weight & Size95 kg; 663 × 394 × 1330 mm Temperature Control± 1 °C accuracy, 150–200 °C running Pre-heat Time< 50 minutes Powder Capacity6.5 kg Supported FormatsSTL, OBJ</p>	1
5	PCB Milling Machine	<p>Cutable Materials: Modeling Wax, Chemical Wood, Foam, Acrylic, Poly Acetate, ABS, PCB, Copper glad, etc Table Size: 225 (X) × 150 (Y) mm or more Drive System: Stepping Motor (X, Y, Z Axis) Operating Speed: 800 mm/min Software Resolution: 0.01 mm/step Position accuracy : 0.01 to 0.02 mm Max Travel Speed (mm/sec)-58 (2.28 ") Drilling (mm)-0.2 -3.175 (8-125 mil) Maximum Drilling Cycles/ Min-50 Spindle Motor: DC Motor Type 380 or More Spindle Speed: Adjustable 20,000 and above rpm or more Tool Chuck Type: Collet Interface: USB or cable Control Commands: RML-1, NC code Power Supply: DC 24V, 2.5A (via AC 100– 240V, 50/60Hz adapter) Power Consumption: Approx. 50 W or more</p>	1
6	CO ₂ Laser Cutting Machine	<p>Working Area: Min 600 x 900 mm or above Laser Type: CO₂ DC Glass Laser Tube/RF Metal Laser Tube Laser Power: 80/100W Wave Length: Upto 10.6 Micrometer Cutting Speed: 30000 mm/min or more Engraving Speed: 64000 mm/min or more XY Axis: LM Guide Rail or equivalent Cooling: Air/ Water Cooling Supply Voltage: 230V/415 V Accessories: CO₂ Focus Lens: 1 No. Mirror 25mm: 3 Nos. Acetone: 1 litre Acrylic sheet: 2 Nos</p>	1
7	Vinyl Printer	<p>Dimensions: 50 cm x 15 cm x 15 cm or above Weight: 15.4 lbs or less Max cut size using machine mat: 11.5 inch x 23.5 inch or more Cut speed: up to 14.1 ips</p>	1

Sr. No	Equipments	Specifications	Qty
8	3D Scanner	<p>Technology: Stereo camera structured light with focusable cameras or equivalent CPU: Quad-core 64-bit SoC, 1.5GHz with integrated GPU RAM: 4 GB Projector: DLP MEMS mirror or equivalent Camera Sensor: Sony 13 MP or better Scan Speed: 4 seconds or more Working Distance : Effective Working Distance: 160mm-1400mm Scan Speed : 980,000points/s, up to 14FPS Align Modes : Feature Alignment, Hybrid Alignment, Texture Alignment, Global Markers Safety : Eye-safe Texture Scan : Yes Interface : USB2.0 or above Outdoor Scanning : Yes Output Formats : OBJ; STL; PLY; P3; 3MF Scanning Environment: Indoor and outdoor (shaded) Texture / Color Scanning: Yes Minimum Capturable Feature Size: 0.2 mm or less Scanner Weight: 500 grams or less Scanner Dimensions: upto 240 × 60 × 60 mm Compatible OS: Any OS supporting a modern web browser</p>	1
9	Lathe Machine cum milling	<p>Centre Width: Up to 400 mm or better Height of Centers: Up to 88 mm Maximum Workpiece Diameter: Up to 100 mm Machine Base: Cross-ribbed surface, high- quality cast iron with ground prismatic guide, capable of fitting milling/drilling attachment Spindle: Supported with adjustable taper roller bearings Spindle Receiver: MK3 or compatible Spindle Drill Hole: Up to 22 mm or better Spindle Concentricity: Up to 5 microns or better Chuck: 3-jaw chuck as per DIN 6386, centrally clamped, 100 mm diameter or better Run Out (without Chuck): Up to 10 microns Sleeve Receiver: MK2, retractable sleeve with scale Spindle Speed Range: Between 50 to 2500 rpm Speed Stages: 6-8 Motor Rating: 550W or better, induction motor, single phase 230V Traverse Cross: Up to 70 mm or better Traverse Longitudinal: Up to 300 mm or better Weight (Complete): Up to 55 kg or more Additional Accessories: Splash guard and chip collecting tray: 1 No. Cutter set with tungsten inserts: 2 Nos. Milling Attachment: 1nos Tungsten disposable tips ten-piece set: 1 No. Sample workpieces (Nylon Rod, Aluminium Rod) Desktop: 1 No.</p>	1
10	CNC Router	<p>Working Area: Min 1300 x 2500 mm Z Axis Working Area: 200 or above Resolution: ±0.03/300mm or more CNC Spindle: 3KW or more Lathe Structure : Welding Steel Structure or equivalent XYZ Structure: Rack Pinion , Ball Screw Linear Rails Max Spindle Speed : Min 18000RPM Table: T-Slot/Vacuum Bed/Water Bed Repeatability: ±0.03 Working Mode: Stepper Motor/Servo Motor Dust Collector : To be included by Vendor Voltage: AC 220V/415V, 50/60 Hz, 3 Phase</p>	1
11	Belt and Disc Sanding Machine	<p>Motor: 230V 50Hz Power: 380W S2 30min No-load Speed: 1450rpm or more Belt Size: 100x914mm or less Disc Size: 150mm or better Table Titing Range: 0°-45° Belt Titing Range: 0°-90° Table Size: upto 190x125mm</p>	1
12	Scroll Saw	<p>Power input: 50 Watt Thickness of Cut: 50 mm (2 inch) Throat: 406 mm (16 inch) Length of Stroke: 18 mm (11/16 inch) Strokes Per Minute: 400-1,600 SPM Overall Length: 600 mm (23-5/8 inch)</p>	1

Sr. No	Equipments	Specifications	Qty
13	Wood Turning Lathe	Motor: 230V~50Hz, 550W, S2:15min or above Max. Disc Diameter: min 75 mm Max. Cutting Length: 450 mm or more Spindle Speed: 5 speeds such as 1600 / 2600 / 3200 RPM etc Material: Cast Iron Bed Height: 0.2 m Cable Length: 0.850 m	1
14	Bench Top Drill Machine	Continuous rating input: Max. 250 W Capacity: Steel: Min 13 mm (1/2") Wood: Min 24 mm (15/16") No Load Speed (RPM): 570, 890, 1,300, 1,900, 2,670(50 Hz), 690, 1,070, 1,560, 2,280, 3,200(60 Hz) Net weight: Max. 20 kg (44.1 lbs.) Power supply cord: 1.75 m (5.7 ft) Additional Accessories: Bench Vise: 1 No., Drill Bit Set 10 Pcs: 1 No	1
15	Portable Welding Machine	Welding Current (at 40°C, 10 min cycle): 120A @ 100%, 150A @ 60%, 200A @ 35% Supply Voltage: 240V +10%, -15%, 1 Phase, 50/60 Hz Open Circuit Voltage: 55V DC ±5V Welding Current Range: 15–200 Amps DC Insulation Class: F Type Ingress Protection: IP21 Dimensions (L×W×H) with Handle: upto 320×120×195 mm Weight (Approx.): 4.3 kg or less	1
16	Computerized Sewing Machine	Motor: 120 W Max Sewing Speed: 860 SPM Power: 220 - 240 V Automation Grade: Automatic Max Stitch Length: 4mm Thread Type: Computerized Weight:7.6 kg Number of Stitches:120 Size/Dimension: 50.8 cm x 29.464 cm x 40.64 cm Maximum Stitch Width: 7 mm Number of Buttonhole Styles:7 LCD Screen Display: Yes Bed Type Free Arm/Flatbed convertible Bobbin Type Drop & Sew Bobbin System	1
17	Filament Dehydrator	Operating Temperature Range: Min 45°C– 70°C Drying Time Setting: 0–48 hours or higher Hot-Air Heating: upto 360° circulation Moving Speed: 300 mm/s or more Power Rating: 160 W Shipping Weight: 2.5 kg	1
18	Reflow Oven	No. of Waves: 7 or higher Heating Type: Infrared IC Heater Max. PCB Width: 300×320 mm or more Power Supply: AC 220V / 50Hz Peak Power: 1500W Cycle Time: 1–8 min or less Temperature Range: 0°C–280°C	1

Sr. No	Equipments	Specifications	Qty
19	Digital multimeter	Display Count: Up to 4000 DC Voltage Range: Up to 1000 V AC Voltage Range: Up to 1000 V DC Voltage Accuracy: $\pm 0.5\%$ or ± 3 digits, whichever is higher AC Voltage Accuracy: Within $\pm 1\% + 3$ digits DC Current Measurement: Up to 10 A AC Current Measurement: Maximum 10 A DC Current Accuracy: $\pm 1.5\% + 3$ digits (approximate) AC Current Accuracy: $\pm 1.5\% + 3$ digits (typical) Resistance Measurement: Up to 40 M Ω Resistance Accuracy: Estimated at $\pm 1.5\% + 3$ digits Capacitance Measurement: Up to 1000 μ F Capacitance Accuracy: $\pm 5\%$ or ± 5 digits Operating Temperature Range: From 0°C up to approximately 40°C Storage Temperature Range: Between -30°C and 60°C Overall Dimensions (H×W×L): Approximately 183×91×49.5 mm Unit Weight: Around 455 grams Safety Compliance: As per IEC 61010-1 & IEC 61010-2-030 standards, suitable for CAT III 600V and CAT II 1000V environments with Pollution Degree 2 classification	5
20	MSO 100 MHz	Bandwidth: Up to 100 MHz Analog Channels: 4 or more Real-Time Sampling Rate: Maximum 1 GSa/s per channel Memory Depth: 10 Mpts per channel Waveform Update Rate: Approximately 120,000 wfms/s Vertical Resolution: 8 bits Vertical Scale: Ranging from 1 mV/div to 10 V/div Horizontal Scale: Spanning 1 ns/div to 100 s/div Spectrum Analyzer Frequency Range: DC to 500 MHz FFT Points: Up to 1M points for enhanced frequency domain resolution Waveform Math Functions: Includes addition, subtraction, multiplication, division, minimum, maximum, root, square, absolute, inverse, derivative, integral, and low-pass filter Trigger Types: Edge, Pulse Width, Video, Pulse Runt, Rise & Fall (slope), Alternate, Timeout, Event-Delay, Time-Delay, and Bus Arbitrary Waveform Generator (AWG): Dual- channel, 25 MHz, supporting various waveforms such as sine, square, pulse, ramp, DC, noise, sinc, Gaussian, Lorentz, exponential rise/fall, haversine, and cardiac AWG Sample Rate: 200 MSa/s AWG Vertical Resolution: 14 bits Display: 8-inch WVGA TFT LCD (800 × 480 pixels) Data Logging Capability: Up to 1000 hours Segmented Memory: Supports up to 29,000 segments for efficient waveform storage and retrieval Connectivity: USB 2.0 (host and device), Ethernet (RJ45), and Go-NoGo BNC Dimensions (W × H × D): 380× 200× 125 mm or above Weight: 2 Kgs or above Safety Compliance: Conforms to IEC 61010-1 and IEC 61010-2-030 standards, suitable for CAT III 600V and CAT II 1000V environments with Pollution Degree 2 classification	1

Sr. No	Equipments	Specifications	Qty
21	Digital oscilloscope	<p>Number of Channels: Up to 2 independent analog inputs Memory Record Length: Up to 10 Mpts for extended waveform capture Bandwidth Limiting: Selectable 20 MHz bandwidth filter Sampling Rate: Maximum of 1 GSa/s real-time equivalent per channel Rise Time: ≤ 3.5 ns depending on probe and settings Display: 7" TFT color LCD with 800×480 resolution Time Base Range: From 5 ns/div to 100 s/div, user-adjustable Vertical Resolution: 8-bit digital resolution Trigger Modes: Automatic, Normal, and Signal-dependent triggering Maximum Input Voltage: 300 Vrms (within safety limits) Input Sensitivity: Within the range of 1 mV/div to 10 V/div Input Coupling Options: Selectable among AC, DC, and Ground Trigger Coupling Modes: Configurable as AC, DC, High-pass, or Low-pass Physical Dimensions: Approximately 350 × 200 × 120 mm or above Unit Weight: 2.5 kg or above Input Impedance: Nominal 1 MΩ // 16 pF Measurement Capabilities: Equipped for automatic parameter extraction, backgroundnoise filtering, and AUTOSET configuration for display scaling (time base/gain) Protocol Decoding Support: Capable of analyzing I2C, SPI, UART, CAN, and LIN communication protocols Standard Accessories: Includes mains power cable, user manual (digital format), and one GTL-16E probe per input channel</p>	1
22	Power supply	<p>Output Configuration: 4-channel design with independent electrical isolation across all outputs Channel Output Ranges: • CH1 & CH2: Adjustable output voltage from 0 to 32V with a current delivery capacity up to 3A • CH3: Variable range 0 to 5V supporting up to 1A • CH4: Output adjustable from 0 to 15V with a load current of up to 1A Constant Voltage Operating Mode Line Regulation: $\leq 0.01\% + 3$ mV (approximate value within rated voltage range) Load Regulation: $\leq 0.01\% + 3$ mV (across rated load variation) Ripple & Noise: ≤ 1 mVrms across full bandwidth Constant Current Operating Mode Line Regulation: $\leq 0.2\% + 3$ mA Load Regulation: $\leq 0.2\% + 3$ mA Ripple Current: ≤ 3 mArms (typical) Safety & Operational Features Output Control: Independent output ON/OFF switching functionality is required Voltage Resolution: Approximately 100 mV (*1) Current Resolution: Approximately 10 mA (*1) Display Parameters Display Units: Four separate displays required for individual channel status visualization Display Type: 4.3-inch LCD (color or monochrome as applicable) Functional Features Tracking Operation: Supported (required for synchronizing output behavior) Auto Series/Parallel: Supported (automatic internal reconfiguration required)Power Requirements Supply Input: 230V AC $\pm 10\%$, 50 Hz Mechanical Specifications Maximum Dimensions (W × H × D): Within 200 mm × 100 mm × 200 mm Maximum Weight: 10 kg or less</p>	1

Sr. No	Equipments	Specifications	Qty
23	Function Generator	<p>Output Function: The equipment shall provide output waveforms including sine, square, triangle, and TTL signals as required.</p> <p>Frequency Range: For sine and square waveforms: approximately 0.1 Hz up to 3 MHz. For triangle waveform: approximately 0.1 Hz up to 1 MHz.</p> <p>Frequency Resolution: Frequency resolution shall be maintained within a maximum of 0.1 Hz.</p> <p>Frequency Stability: The frequency stability shall be within ± 20 ppm (parts per million).</p> <p>Frequency Accuracy: The frequency accuracy shall be maintained within ± 20 ppm.</p> <p>Frequency Aging: Frequency aging shall not exceed ± 5 ppm per annum.</p> <p>Amplitude Range: Output amplitude shall be up to 10 V peak-to-peak (V_{p-p}) into a 50 Ω load.</p> <p>Amplitude Accuracy: Amplitude accuracy shall be within $\pm 20\%$ at maximum amplitude setting.</p> <p>Output Impedance: Nominal output impedance shall be 50 Ω with a tolerance of $\pm 10\%$.</p> <p>Attenuator: A single-step attenuator of -40 dB ± 1 dB shall be provided.</p> <p>Display: A 6-digit LED display shall be incorporated for parameter indication.</p> <p>Output Control: Output shall be controlled via an ON/OFF selector switch.</p> <p>Power Source: The device shall operate on an AC supply of 240 V, 220 V, or 110 V $\pm 10\%$, with frequency 50/60 Hz.</p> <p>Ambient Operating Temperature: Normal operation shall be ensured within the ambient temperature range of 0 $^{\circ}$C to 40 $^{\circ}$C. Dimensions: Maximum dimensions shall not exceed 255 mm (W) \times 95 mm (H) \times 295 mm (D).</p> <p>Weight: Maximum device weight shall be within 2.5 kg.</p>	1
24	Bench Top Multimeter	<p>DC Voltage: Range: 500 mV to 1000 V across 5 ranges. Accuracy: $\pm(0.03\% \text{ rdg} + 4 \text{ digits})$.</p> <p>Input impedance: 10 MΩ. AC Voltage (True RMS): Range: 500 mV to 1000 V across 5 ranges. Accuracy: $\pm(0.5\% - 5\% \text{ rdg} + \text{digits})$ depending on frequency and range. Input impedance: 10 MΩ.</p> <p>DC Current: Range: 500 μA to 20 A across 6 ranges. Accuracy: $\pm(0.02\% - 0.3\% \text{ rdg} + 2 \text{ digits})$ depending on range.</p> <p>AC Current (True RMS): Range: 500 μA to 20 A across 6 ranges. Accuracy: $\pm(0.5\% - 1\% \text{ rdg} + \text{digits})$ depending on frequency. Resistance: Range: 500 Ω to 20 MΩ across 6 ranges. Accuracy: $\pm(0.1\% - 0.3\% \text{ rdg} + \text{digits})$ depending on range.</p> <p>Diode Test: Max forward voltage 1.5 V, open voltage 2.8 V.</p> <p>Capacitance: Range: 5 nF to 50 μF. Accuracy: $\pm(2\% \text{ rdg} + 4 \text{ digits})$.</p> <p>Frequency: Input level varies by range; functions include Auto/Manual Range, Max, Min, dBm, Rel, Hold.</p> <p>Continuity Beep: Threshold $< 5 \Omega$.</p> <p>Display: Dual 7-segment LED, 0.4" and 0.5". Power Source: AC 100/120/230 V $\pm 10\%$, 50/60 Hz.</p> <p>Dimensions & Weight: Approximately 251 \times 91 \times 291 mm; 2.6 kg.</p>	1

Sr. No	Equipments	Specifications	Qty
25	Non-Contact Voltage Tester	<p>Function: Non-contact AC voltage detection tester.</p> <p>Voltage Detection Range: Approximately 90 V to 1000 V AC.</p> <p>Detection Method: Capacitive, with visual and audible indication.</p> <p>Sensitivity: Adjustable sensitivity for different voltage ranges.</p> <p>Response Time: Instantaneous detection within standard operating conditions.</p> <p>Indicators: Bright LED indicators and audible beep for voltage presence.</p> <p>Operating Environment: Suitable for use in ambient temperatures from 0 °C to 40 °C. Power Source: Powered by standard batteries (typically 2 × AAA or equivalent).</p> <p>Safety Standards: Complies with IEC/EN 61010-1 CAT III 1000 V safety standards.</p> <p>Dimensions: Compact, handheld design suitable for field use (approx. 150 mm × 30 mm × 25 mm).</p> <p>Weight: Lightweight, approximately 150 g for ease of portability.</p>	5
26	LCR Meter	<p>Display: Approximately 2.8" TFT touch LCD screen.</p> <p>Resolution: 25,000 or above counts resolution on both primary and secondary displays.</p> <p>Basic Accuracy: Within ±0.2% under standard conditions.</p> <p>Test Frequencies: Six or eight selectable frequencies depending on model variant.</p> <p>Measurement Combinations: Up to 15 different measurement combinations available.</p> <p>Test Level: Selectable AC test levels approximately 0.3 V, 0.7 V, and 1 V rms; DC test level selectable at ±1 V.</p> <p>Measurement Speed: Selectable measurement speeds of approximately 10 measurements per second (fast) and 2.5 measurements per second (slow).</p> <p>Auto LCR Mode: Automatic identification and measurement of component types within supported ranges.</p> <p>Data Hold: Feature available to hold measured data on display.</p> <p>Interface: USB virtual COM port provided for remote communication capabilities.</p> <p>Software: Datalogging software available for data capture and analysis.</p>	1
27	Soldering Station	<p>Power Rating: Approximately 60 W maximum output power.</p> <p>Temperature Range: Adjustable from approximately 200 °C up to 480 °C. Temperature Stability: Within ±2 °C under normal operating conditions.</p> <p>Heating Element: Ceramic heating element for rapid heat-up and efficient temperature maintenance.</p> <p>Display: Digital or analog temperature display (depending on variant) for precise temperature control.</p> <p>Temperature Control: Adjustable via knob or digital interface with fine resolution.</p> <p>Power Supply: AC 220 V ±10%, 50/60 Hz. Safety Features: Thermal cutoff and overload protection within required standards.</p> <p>Dimensions: Compact design with 100 mm × 100 mm × 90 mm (W × H × D) or above</p> <p>Weight: Approximately 1.5 kg for ease of portability and bench use.</p>	3
28	Digital Microscope	<p>Specification: Magnification: 1600X Light source: 8 LED lights Resolution: 1920×1080, 640*480 Pixel: 30W</p> <p>Focal length: 3-40mm manual adjustment Support Android 4.2 or above/widows/Mac system</p>	1

Sr. No	Equipments	Specifications	Qty
29	Soldering Rework Station	<p>Soldering Iron Power: Up to approximately 60 W output power with temperature adjustable within approximately 200 °C to 480 °C range. Heating Element: Needle bit with MCH heater providing rapid heat-up and stable temperature control within ±2 °C.</p> <p>Hot Air Blower Power: Up to approximately 500 W output power with temperature adjustable within approximately 200 °C to 450 °C range, multiple nozzles included.</p> <p>Hot Air Features: Auto-pause function on placement in cradle, airflow adjustable within operational limits.</p> <p>DC Power Supply: Provides output voltage approximately 15 V up to 2 A maximum current plus 5 V USB output for auxiliary power.</p> <p>Control: Microcontroller-based system with LED indicators for temperature and mode selection.</p> <p>Safety: ESD-safe design compliant with applicable standards.</p> <p>Build: Metallic body with powder coating, approximate dimensions 280 mm × 180 mm × 140 mm (W × H × D).</p> <p>Weight: Approximately 3.5 kg.</p> <p>Power Source: AC 220 V ±10%, 50/60 Hz. Accessories: Includes soldering iron with needle bit, hot air blower with 3 nozzles, iron stand with sponge, hot air cradle, patch cord, and power cord.</p> <p>Operating Temperature: Suitable for ambient temperature approximately 0 °C to 40 °C</p>	1
30	Hand Drill Machine	<p>Rated Input Power: Approximately 500 W or above maximum power consumption.</p> <p>Bit Holder: Standard 1/2"-20 UNF thread type.</p> <p>No-Load Speed (1st Gear): Adjustable from 0 up to approximately 3,000 rpm.</p> <p>Power Output: Approximately 300 W continuous output power.</p> <p>Weight: Approximately 1.7 kg total device weight.</p> <p>Impact Rate at No-Load Speed: Variable from 0 up to approximately 48,000 bpm.</p> <p>Rated Torque: Approximately 1.4 Nm maximum torque output.</p> <p>Drill Spindle Connecting Thread: Standard 1/2"-20 UNF thread.</p> <p>Chuck Capacity (Min/Max): Approximately 1.5 mm minimum to 13 mm maximum.</p>	2
31	Cordless drilling	<p>Torque (soft/hard/max.): Min 21/50/- Nm No-load speed (1st gear / 2nd gear): Min 0 – 500 / 0 – 1,900 rpm Weight incl. battery: 1.3 kg or less Max. impact rate: 27,000 bpm</p> <p>Battery type: Lithium-Ion or equivalent Chuck capacity, min./max.: 1.5 / 13 mm Weight excl. battery: 0.99 kg</p> <p>Torque settings: 20+2 or better</p>	2
32	Jig Saw	<p>Rated Input Power: Approximately 500 W maximum power consumption.</p> <p>Voltage, Electrical: Nominal 230 V AC supply.</p> <p>Saw Stroke Length: Approximately 20 mm stroke length.</p> <p>Stroke Rate at No Load: Adjustable within approximately 800 to 3,100 spm (strokes per minute).</p> <p>Weight: Approximately 2.08 kg total weight. Bevel Angle: Adjustable within approximately -45° to 45° range.</p>	2

Sr. No	Equipments	Specifications	Qty
33	Miter Saw	<p>Rated Input Power: Approximately 1,750 W maximum power consumption. Saw Blade Diameter: Approximately 254 mm nominal diameter. Mitre Setting: Adjustable up to approximately 47° left and 52° right. Bevel Setting: Adjustable up to approximately 45° left and 0° right. Saw Blade Bore Diameter: Approximately 25.4 mm standard bore. Cutting Capacity at 0°: Approximately 90 mm × 130 mm maximum cross-section. Cutting Capacity at 45° Mitre: Approximately 90 mm × 91 mm maximum cross-section. Cutting Capacity at 45° Bevel: Approximately 60 mm × 130 mm maximum cross-section. Tool Dimensions (W×L×H): Approximately 477 mm × 559 mm × 567 mm. No-Load Speed: Fixed at approximately 5,000 rpm. Weight: Approximately 11.1 kg.</p>	1
34	Hot air gun	<p>Rated Input Power: Approximately 1,800 W maximum power consumption. Voltage, Electrical: Nominal 230 V AC supply. Weight: Approximately 0.75 kg. Working Temperature Range: Adjustable within approximately 60 °C to 550 °C. Heat-Up Time: Approximately 1 second to reach target temperature. Airflow: Adjustable within approximately 350 to 550 liters per minute. Airflow Control: Three selectable airflow settings.</p>	2
35	Table saw	<p>Rated input power: Max 1800 W Incline setting: 45 ° L / 0 ° R Table size: Up to 555 x 555 mm Saw blade diameter: 254 mm Cutting height 90°: 80 mm Cutting height 45°: 55 mm Saw blade bore diameter: 30 mm Weight 24.4 kg or less Max. cutting capacity on the right: 545 mm No-load speed: 4300 rpm Cutting height 90°: 80 mm Cutting height 45°: 55 mm</p>	1
36	Bench grinder	<p>Grinding wheel diameter: min 150 mm Rated input power: 350 W or more Grinding wheel widths: 20 mm or more No-load speed: upto 3,000 rpm Grinding wheel bore: 20 mm/2cm Grit 24, 60 or more Weight: 10 kg or less</p>	1
37	Angle Grinder	<p>Rated Input Power: Approximately 670 W maximum power consumption. No-Load Speed: Approximately 11,000 rpm. Disc Diameter: Approximately 100 mm nominal diameter. Grinding Spindle Thread: Standard M10 thread. Weight: Approximately 1.5 kg. Switch: Lockable switch for operational safety.</p>	1
38	Straight Grinder	<p>Rated Input Power: Max 300 W power consumption. No-Load Speed: Up to 28,000 rpm. Voltage, Electrical: Nominal 230 V AC supply. Spindle Collar Diameter: Approximately 41 mm. Weight: Around 1.4 kg. Maximum Grinding Tool Diameter: Up to 25 mm. Maximum Collet Diameter: Up to 8 mm. Switch: Lockable switch for enhanced safety.</p>	1
39	Circular Saw	<p>Rated Input Power: Approximately 1,400 W maximum consumption. Saw Blade Diameter: Nominal 184 mm diameter. Saw Blade Bore Diameter: About 20 mm standard bore size. Guide Rail Compatibility: Not compatible with guide rails. No-Load Speed: Typically 5,200 rpm. Weight: Around 4.1 kg</p>	1
40	Blower	<p>Rated Input Power: Max 650 W power consumption. Weight: Approximately 1.7 kg. Voltage, Electrical: Nominal 230 V AC supply. Sound Pressure Level: Around 103 dB(A). Sound Power Level: Approximately 95 dB(A). Uncertainty (K): Within ±3 dB</p>	1

Sr. No	Equipments	Specifications	Qty
41	Cordless Screw Driver	<p>Battery Capacity: Around 1.5 Ah nominal capacity. Torque (Soft/Hard/Max): Approximately 14 Nm / 30 Nm / Maximum not specified. No-Load Speed (1st Gear / 2nd Gear): Ranges from 0 up to 400 rpm and 0 up to 1,500 rpm respectively. Battery Type: Rechargeable Lithium-Ion battery. Chuck Capacity (Min/Max): From approximately 0.8 mm up to 10 mm. Weight (Excluding Battery): About 0.8 kg. Torque Settings: 20 plus 1 adjustable settings.</p>	1
42	Vacuum Cleaner	<p>Rated Input Power: Approximately 1,100 W maximum power consumption. Weight: Around 6 kg total weight. Container Volume (Net): Approximately 10 liters capacity. Voltage, Electrical: Nominal 230 V AC supply. Container Volume (Gross): Approximately 15 liters total volume. Container Volume (Net, Water): About 8 liters capacity for water. Filter Surface Area: Around 2,300 cm² effective filtration area. Airflow Rate (Turbine): Approximately 53 liters per second. Vacuum Pressure (Turbine): Up to 270 mbar vacuum pressure. Number of Wheels: Four wheels for mobility.</p>	1
43	Random orbit sander	<p>Rated Input Power: Up to 280 W maximum consumption. Sanding Pad Diameter: Nominal 125 mm diameter. Orbit Diameter: Approximately 2.6 mm orbital diameter. Weight: Around 1.4 kg. No-Load Speed: Adjustable within 7,500 to 12,000 rpm range. Orbital Stroke Rate: Between 15,000 and 24,000 orbits per minute (opm). Eccentricity: Approximately 1.3 mm.</p>	1
44	Planer	<p>Rated Input Power: Not exceeding 710 W under nominal operating conditions. Planing Width: Approximately 82 mm effective width capacity. Planing Depth: Within the range of up to 2.6 mm maximum depth per pass. Weight: Circa 2.8 kg total unit mass. Adjustable Rebating Depth: Maximum adjustable depth of approximately 9 mm. No-Load Speed: Operating speed typically around 18,000 rpm.</p>	1
45	Cordless Vacuum Cleaner with Starter kit	<p>Battery Voltage: Rated at approximately 18.0 V nominal voltage. Weight Excluding Battery: Around 1.3 kg without battery attached. Container Volume: Approximately 0.7 liters net capacity. Filter Surface Area: Roughly 55 cm² filtration surface. Maximum Airflow Rate (Turbine): Up to 10 liters per second. Maximum Vacuum Pressure (Turbine): Not exceeding 60 mbar under standard conditions. Operating Time (18 V Battery): Typically 7 minutes per Ah of battery capacity.</p>	1
46	Rotary Tool Kit	<p>Rated Power Input: Approximately 175 W within nominal voltage range. Voltage: Operates within 220 to 240 V AC supply. Weight: Around 0.66 kg total mass. Length: Approximately 24 cm overall length. Width: About 4.1 cm nominal width. Depth: Roughly 4.3 cm depth dimension. No-Load Speed: Variable speed ranging from 5,000 up to 35,000 rpm. Battery Technology: Not applicable (n.a.). Speed Setting: Fully variable speed control as required. Accessory Quick Change System: Equipped with multi chuck for rapid accessory interchange. Vibration Level: Approximately 18 m/s² measured vibration</p>	2
47	Rubber Grip Hacksaw	<p>Depth of Throat: Approximately 98 mm (3.85 inches) nominal depth. Blade Length: Around 254 mm (10 inches) standard length.</p>	2

Sr. No	Equipments	Specifications	Qty
48	Hacksaw Mini	Blade Length: Approximately 10 inches nominal length. Handle Material: Constructed from metal as standard. Overall Length: Around 11 inches total length.	2
49	Claw Hammer Steel Shaft	Weight: Approximately 8 oz (220 grams) nominal weight. Dimensions: Around 27.8 cm × 12.4 cm × 3.6 cm (L × W × H) overall size	2
50	Ball Pein Hammer	Weight: Approximately 110 grams nominal weight. Dimensions: Around 32.6 cm × 10 cm × 2 cm (L × W × H) overall measurements.	5
51	Rubber mallet	Weight: Approximately 450 grams nominal weight. Dimensions: Around 33.6 cm × 9.6 cm × 6.2 cm (L × W × H) overall size.	5
52	Ring spanner set 12Pcs	Weight: 3.08 Kg nominal weight. Quantity: 12 pcs per set. Size: 6 mm to 32 mm overall range.	1
53	Open end spanner set 12Pcs	Weight: Approx 1.74Kg nom.wt. Qty: 12pcs/set. Size: 6mm-32mm overall dims.	1
54	Combination Spanner set 8Pcs	Weight: Approx 649g nom.wt. Qty: 8pcs/set.	3
55	Allen key set 10pcs	Hex Key Size: 1.5, 2, 2.5, 3, 4, 5, 5.5, 6, 8, 10mm; Qty: 10pcs/set	2
56	Allen key set 12pcs	Ball Key Size: 1/16", 5/64", 3/32", 7/64", 1/8", 9/64", >5/32", 3/16", 7/32", 1/4", 5/16", 3/8" Qty: 12pcs/set	2
57	Combination plier	Weight: Approx 422g nom.wt. Size: 8"/200mm nominal	2
58	Long nose plier	Weight: Approx 399g nom.wt. Size: 180mm/6" nominal	2
59	Circlip straight 5"	Weight: Approx 399g nom.wt. Size: 130mm/5" nominal	2
60	Circlip bent	"Weight: Approx 399g nom.wt. Size: 130mm/5" nominal"	2
61	Diagonal Cutter	"Weight: Approx 239g nom.wt. Size: 180mm nominal"	2
62	Wire Stripper	Weight: Approx 281g nom.wt. Size: 130mm nominal	2

Sr. No	Equipments	Specifications	Qty
63	Adjustable spanner	Size: Upto 150 mm	2
64	Pipe wrench	Size: Max 300 mm	2
65	C – clamp	Size: Upto 75 mm	4
66	C-clamp	Size: Upto 150 mm	4
67	Snap- off Knife	Size:18 mmm	2
68	16pcs screw driver set	Pieces Per Set: 16 pcs	1
69	6pcs precision screw driver set	Pieces Per Set: 16 pcs	2
70	Max steel snip cutter	Length: 250 mm	2
71	PVC Pipe cutter	Length: 42 mm	2
72	Hot Glue Gun	Power: 40 W	4
73	Small file set	Length: 160 mm	2
74	Big file set	Length: 200 mm	2
75	Chisel set	Weight: 340 gm	2
76	Punch set	Weight: 390 gm	2
77	Bench vise	Base Type: Fixed Size:2-3½" nominal JawWidth:60mm	2

Sr. No	Equipments	Specifications	Qty
78	Router Bit Starter Kit	Pieces Per Set: 15 pcs	1
79	Drill bit set	WAF(mm):1,1.5,2,2.5,3,3.5,4,4.5,5,5.5,6,6.5,7,7.5,8,8.5,9,9.5,10,10.5,11,11.5,12,12.5,13 Wt:~1.3Kg nom.wt Sz(mm):205×115×55 overall	2
80	Baby vise	Vice Type: Bench Size:2" nominal JawWidth:50mm	2
81	Ratchet Set	Vice Type: Bench Sz:2" nominal; Jaw:50mm	2
82	Pegboard		5
83	Digital Vernier Caliper	Product Type: Digital Calliper Meas.Range:0–150mm / 0–6" Resolution:0.01mm	2
84	Micrometer	Resolution:0.001mm/0.00005" Meas.Range:0–25mm/0–1"	1
85	Steel Rule 300mm	Product Type: Steel Rule ScaleSize:12"/300mm Material: Stainless Steel	5
86	Steel Rule 600mm	Product Type: Steel Rule ScaleSize:24"/600mm Material: Stainless Steel	5
87	Engineering Square	Size:150×80mm nominal Material: Carbon Steel	2
88	Meter Tape 30m	Length: 30 m	1
89	Measuring Tape 3M	Length: 3 m	3
90	Measuring Tape 5M	Length: 5 m	3
91	Spirit Level	Vials:3 Accuracy:0.5mm/m Length:300mm Product Type: Level	3
92	Goggle	Goggle – Industrial Standard Make	5

Sr. No	Equipments	Specifications	Qty
93	Apron	Apron - Standard Make	5
94	Ear Muff	Earmuff – Industrial Standard Make	5
95	Mask	Mask – Industrial Standard Make	50
96	Fire Extinguisher	Fire Extinguisher– Industrial Standard Make	6
97	First Aid Kit	First Aid Kit – Industrial Standard Make	2
98	Gloves Pair	Gloves – Industrial Standard Make	10
99	Normal Oven	Oven Cap: 20L or more Type: Solo Door: Side Swing Child Lock: Yes Completion Beeper: Yes Power Levels: upto 5 Control: Membrane Type Cavity Mat: Anti-Bacterial Dims(mm):455×252×320 PowerOut:700W or less	1
100	Refrigerator	Capacity:183L or more AnnualEnergyConsumption:148kWh/Year or less RefrigeratorFreshFoodCapacity:165L or more Freezer Capacity: min 18L BottleCount:5 or more NoiseLevel:40dB or less Installation Type: Freestanding	1
101	Smart Board	Display Size: Approx 75Inch (190 cm) Up to Resolution: 4KUHDorHigher Brightness: Min 350 nits; Typ400nitsApprox Contrast Ratio: Typ 1200: 1Upto Response Time: Approx 8ms Viewing Angle: Approx178DegreesWide WorkingFrequency:1.5GHzNominal RAM:4GBOrMore InternalStorage:32GBMin OS: Android Based HDMI: 3Ports USB: 2Ports Sensing Type: Infrared Touch Frame Surface Protection: 4mm Toughened Glass Or Equivalent Infrared Touch Points: 20Approx Voltage:DC+5V±5%Range OPS: Optional	1
102	Projector	Projection Tech: RGB liquid crystal shutter projection (3LCD) Up to Connectivity: USB Type B: 1port (FirmwareUpdate/Copy OSD) Approx AnalogInput:D-Sub15pin:1port Digital Input: HDMI:1port Projection Lens: Type: No Optical Zoom/Focus (Manual)Nominal FocalLength:16.70mm Approx FNumber:1.44 Nominal Zoom:1.44-1.95 Ratio (Wide to Tele) ThrowRatioRange:1.00–1.35(Digital Zoom Approx	1

Sr. No	Equipments	Specifications	Qty
103	Printer	Functions: Print, Scan, Copy Printer Type: Laser Nominal Dims(mm):409×398.5×267Approx Weight:9.7KgNominal PrintSpeed:Upto30ppm(A4Size)Approx Warranty:1YearOn-Site PrintResolution:600×600dpi,HQ1200(2400× 600dpi) Quality Approx 2Sided-Duplex- PaperType:Plain,Thin,RecycledApprox 2Sided-Duplex-PaperSize:A4 PaperHandling:Tray#1- PaperType:Plain,Thin,Recycled Tray#1- MaxCapacity:Upto250Sheets(80g/m²)Approx PaperOutput:Upto100Sheets(80g/m²)FaceDownTray;OneSheetFaceUpTrayApprox Copy- Colour /Mono: Yes/Yes Multiple Copies: Sorts/StacksUpto99PagesApprox Enlarge/Reduce:25%- 400%(In1%Steps)Approx CopyResolution:600×600dpi 2Sided-Duplex- CopyPaperType:Plain,Thin,Recycled 2Sided-Duplex-CopyPaperSize:A4 Scan- ResolutionInterpolated:Upto19200×19200dpiApprox Scan- ResolutionGlass:Upto600×2400dpiApprox Connectivity:Hi-SpeedUSB2.0 DisplayType:16Chars×2Lines MemoryCapacity:32MBAprox PowerSource:220-240VAC50/60Hz PowerConsumption-Ready:Approx60W PowerConsumption-Sleep:Approx6.6W PowerConsumption-Off:Approx0.08W NoiseLevel:50dB(A)Approx	1
104	Desktop	CPU: INTEL CORE I7-12THGEN or Higher RAM:8GB+512GB SSD or more Conn: LAN+WIFI+BLUETOOTH+KEYMOUSE Display:20" DESKTOP MONITOR	5
105	3D printer Filament	Weight Kg: 1 Approx Melt Flow Index: 2 (190°C/2.16kg) Nominal FilamentLength:330mApprox Dim Accuracy: +/-0.1mmApprox Roundness Accuracy: +/-0.5mmApprox SpoolInnerDia:55mmNominal SpoolOuterDia:200mmApprox SpoolWeight:300gNominal SpoolWidth:65mmApprox	10
106	Acrylic Sheet 3mm, 4ft x 4ft		20
107	Acrylic Sheet 4mm, 4ft x 4ft		20
108	Acrylic Sheet 5mm, 4ft x 4ft		20
109	Foam Sheet 8mm, 4ft x 4ft		2
110	Foam Sheet 10mm, 4ft x 4ft		2
111	Foam Sheet 12mm, 4ft x 4ft		2
112	Foam Sheet 15mm, 4ft x 4ft		2

Sr. No	Equipments	Specifications	Qty
113	Ply Board 5mm, 2ft x 4ft, 8mm, 12mm, 18mm each		5
114	Nylon Rod 10mm, 1m		5
115	Nuts (3mm, 4mm, 5mm, 6mm, 8mm, 10mm, 12mm) Pack of 100		1
116	Bolts (3mm, 4mm, 5mm, 6mm, 8mm, 10mm, 12mm) dia 1" Inch Pack of 100		1
117	Screws (3mm, 4mm, 5mm) Pack of 100		1
118	Washers (3mm, 4mm, 5mm, 6mm, 8mm, 10mm, 12mm) Pack of 100		1
119	Studs (6mm, 8mm) 1 Meter		2
120	Nails (1", 2", 3", 1.5", 5") Pack of 100		1
121	Fevicol 2Kg		10
122	2 Way Tape		20
123	PVC Pipe .75", 10ft		10
124	PVC Pipe 1", 10ft		10
125	PVC Pipe 1.5", 10ft		10

Sr. No	Equipments	Specifications	Qty
126	PVC Pipe 2.0",10ft		10
127	Aluminium channels (L, C, Box, strip length 12ft)		2
128	PCB Drill Bit 0.4mm		10
129	PCB Drill Bit 0.8mm		10
130	PCB Drill Bit 1mm		10
131	Drill Bit 4mm		10
132	Drill Bit 5mm		10
133	Drill Bit 6mm		10
134	Arduino UNO R3		5
135	Arduino NANO		5
136	Arduino Mega		3
137	Raspberry Pi Model 4B, 4GB		3
138	ESP8266 NodeMCU		2
139	ESP32 Development Board		2
140	Beaglebone blu		1

Sr. No	Equipments	Specifications	Qty
141	Beaglebone Black		1
142	Voltage Regulator Module		2
143	Mini Micro submersible Water Pump		2
144	Piezoelectric Plate		2
145	8*8 LED Matrix Module		2
146	Bluetooth		2
147	7 Segment LED Display		2
148	GSM/GPRS/GPS Module		2
149	Laser Module		2
150	LDR Module		2
151	4×4 Matrix Keypad		2
152	Joy Stick Module		2
153	Active Buzzer (BIG)		2
154	Active Buzzer (SMALL)		2
155	Motor Driver		2

Sr. No	Equipments	Specifications	Qty
156	Sound Playback Module		2
157	BO Motors		10
158	Vibrating Motor		10
159	Capacitive Touch Switch		2
160	IR Sensors (Obstacle Sensors)		2
161	Triple Axis Magnetometer		2
162	Humidity Sensor		2
163	MQ-2		2
164	MQ-3		2
165	MQ-4		2
166	MQ-5		2
167	MQ-7		2
168	Ultrasonic Sensor Module		2
169	Triple Axis accelerometer		2
170	PIR Motion Detector Module		2

Sr. No	Equipments	Specifications	Qty
171	Pulse Rate Heart Sensor		2
172	Soil Moisture Sensor		2
173	Touch Sensor		2
174	Rain Drop Sensor		2
175	Flex Sensor		2
176	Temperature Sensor		2
177	Force Pressure Sensor		2
178	Colour Recognition Sensor		2
179	Water Flow Sensor		2
180	Sound Sensor		2
181	IR Sensor Array for Line Following		2
182	RFID Reader-Tags		2
183	RF Modules Tx& Rx 315 MHz ASK		2
184	Stepper motor with Driver Board		2
185	Servo Motor 360 rotation		10

Sr. No	Equipments	Specifications	Qty
186	Servo Motor 180 rotation		10
187	Metal Gear Servo Motor (180° Rotation)		10
188	Solder Wire 100grm		10
189	Solder Flux		10
190	830 Points Solderless Breadboard		5
191	400 Points Solderless Breadboard		5
192	Copper Clad Board single side		10
193	Copper clad board double side		10
194	Male to Male Breadboard Jumper		10
195	Female to Female Breadboard Jumper		10
196	Male to Female Breadboard Jumper		10
197	Manual PCB Drilling Machines (3 Nos.)		3
198	PCB power Drilling Machines (2 Nos.)		1
199	Nylon mallet(5 pcs)		3
200	Dremel multi tool kit (2 Nos.)		2

Sr. No	Equipments	Specifications	Qty
201	Tool Wall covering Perforator(3 pcs)		3
202	Dremel Moto Saw		1
203	Power Return Measuring Tape (5 Nos.)		5
204	Dremel Cordless Rotary Tool		1
205	Power Router		1
206	Impact Drill(2 units)		2
207	Hot Air Blower With Soldering Iron		5
208	Tin Cutter With Spring		-
209	Cutting Mats		5
210	Micromer		3
211	Allen Set Wrench		5
212	Tongue and Groove Pliers		5
213	Fish Tape		2
214	Flashlights		2
215	Glass Cutter		1

Sr. No	Equipments	Specifications	Qty
216	Clothes Iron		5
217	Ratchet Clamp 8"/200mm		10
218	Baby Vice 60mm		3
219	Clothes Iron(5 units)		5
220	Carpentry Boring bits		1
221	Electronic components		10
222	USB Cables		10
223	Radium Cutter Knives		10
224	Glue Sticks		50
225	Hack Saw Blades		10
226	Hack Saw Blades		10
227	9V Battery Snaps		20
228	LAN Cables		5
229	9V Batteries		20
230	Magnifying glass with stand-2 Nos.		2

Sr. No	Equipments	Specifications	Qty
231	Mixed Signal Oscilloscope		1
232	Signal generator		1
233	QUADCOPTER Assembly Kit		1
234	GPIO Modules	Ethernet controlled relay, Wi-ficonrolled relay 8 channel	1
235	Electric Bicycle	motor & Accessories	1
236	Granite surface plate	(630*630*80mm Grade "0") with stand	1
237	Fuse	16 Amps	10
238	MCB Single Pole	6 Amps	10
239	MCB Single Pole	16 Amps	10
240	MCB Double Pole	32 Amps	10
241	RCCB	16 Amps	10
242	RCCB	25 A/30 mA	10
243	Wire	1 Sq.mm	3 Coils
244	Wire	0.75 Sq.mm	3 Coils
245	Wire	2.5 Sq.mm	3 Coils

Sr. No	Equipments	Specifications	Qty
246	Tester	Taparia	15
247	Clamp	NA	50
248	Screw Driver	Taparia	10
249	Cutting Plier	Taparia	10
250	Distribution Box	Legrand - 8 Way MCB DB	1
251	Wire Cutter	Taparia	10
252	Pattern Holder	NA	1
253	One Way Switch	Legrand	25
254	Two Way Switch	Legrand	25
255	Switch Box	Legrand - 2 & 4 module	Each 10
256	Incadescent Lamp	50 Watts	25
257	Fluorescent Lamp	40 Watts	10
258	Energy Meter	5-30 Amps	10
259	PVC Wiring Pipe	0.5 mm-10 Feet	40
260	Lamp Holder	NA	15
261	Calling Bell	NA	10

Sr. No	Equipments	Specifications	Qty
262	L Bend	NA	15
263	T Bend	NA	15
264	Multimeter		10
265	Single Phase Motor	0.37 KW, 0.5 HP, 1500 RPM	2
266	DOL Starter	0.5 HP (4-6.5A), 220 Volts (AC)	2
267	ESP32 Microcontrol	NA	2
268	AC Current Sensor	ACS712	2
269	AC Voltage Sensor	ZMPT101B	2
270	Relay Module	1 Channel	2
271	Connecting Wires /	NA	30
272	Solar Charge Control	12 V Input & 10 Amps	2
273	Battery	12 V & 26 Ah	2
274	Inverter	150 VA	2
275	Lamp Load	12 W LED Bulb	6
276	Battery Charger	5 Amps	2
277	Glass Fuse	10 Amps	2
278	Solar Panel	60 Cells (1.6-1.7 meters tall by 1 meter wide)	2
279	Hair Dryer	Philips HP8144-06	2
280	Mixer Grinder	Bajaj GX15	2
281	Exhaust Fan	Crompton Axial Air High-Speed	2

Terms and Conditions

The following Terms and Conditions apply to all bidders participating in the tender for the supply, installation, and commissioning of equipment, tools, and machines for the establishment of an AICTE IDEA Lab as per the AICTE guidelines and General Financial Rules 2017 (GFR2017). All prospective vendors are required to read and comply with these terms in their entirety.

1. General Information

All equipment and materials must be delivered in the quantities and specifications as mentioned in the purchase order issued by the purchaser. The delivery location will be specified in the purchase order (**Nandha Engineering College, Perundurai, Erode-638052, Tamilnadu**). The entire contract shall remain valid for a period of three (3) months from the date of award.

Quotations submitted by bidders must remain valid for a minimum of 90 days from the final date of submission. Any quotation that does not meet this validity period will be considered non-compliant.

2. Bid Submission Guidelines

Bids may be submitted via email (digitally signed) and in hard copy form, as specifically mentioned in the tender notice. All quotations must be printed on the bidder's official letterhead and duly signed by an authorized representative.

A separate bid shall be submitted for technical and financial. Each bid must be complete in all respects and must include the following mandatory documents:

- Detailed Profile of the Bidder, highlighting experience and key competencies.
- Copy of the Company/Firm Registration Certificate.
- Copy of valid GST Registration Certificate.
- Copy of submitted GST return (at least up to March 2025).
- Copy of valid PAN Card.
- Chartered Accountant's Certificate for turnover for FY 2022–23, 2023–24, and 2024–25.
- CA-certified and audited Balance Sheets and Financial Statements (Form 3CB/3CA) for the last three financial years.
- Copies of Work Completion or Experience Certificates of similar completed works.
- Valid Shop Establishment License or Factory License.
- Genuine Manufacturer Authorization Form (MAF), which will be subject to verification with the respective OEM.
- Bidder should provide an Escalation Matrix for service and after sales support.
- Valid EPF, ESIC, and Professional Tax Registration Certificates (where applicable).
- Income Tax Return Acknowledgements for FY 2022–23, 2023–24, and 2024–25.
- Declaration/Affidavit (on Rs.500/- Stamp Paper) regarding no blacklisting from IITs/NITs/Govt. Offices/PSUs/Autonomous Bodies.

- Complete, signed, and stamped tender document including amendments and deviation sheets, if any (to be uploaded online only).
- Declaration of agreed specifications on company letterhead duly signed and stamped.
- Any other documents in support of technical eligibility.
- All bidders are required to quote for all the items listed in the Bill of Quantities (BoQ). Partial or item-wise quotations will be summarily rejected. Each bidder is allowed to submit only one quotation per package; multiple submissions from a single bidder will lead to disqualification.

3. Technical Documentation and Compliance

The bidder must furnish complete technical documentation for each quoted item. This includes detailed product specifications, installation manuals, operation and maintenance manuals. The bidder is also required to submit a layout/design proposal aligned with the lab setup requirements, highlighting compliance points against the tender specifications.

Original technical brochures or scanned versions of product catalogs should be submitted with the bid. Wherever available, URLs to the OEM's official product page should also be provided for cross- verification.

Each bidder must clearly mention the make, model, and complete technical specifications for the equipment being offered. A compliance sheet responding to each technical requirement outlined in the tender must be prepared and duly signed.

4. Eligibility and Qualification Criteria

All bidders must be OEMs or authorized partners/distributors with valid authorization for the products they are quoting. Authorization letters must be submitted on the OEM's official letterhead.

Bidders must demonstrate relevant experience by submitting a minimum of three Purchase Orders (executed within the last five years) for similar equipment supplied to academic, R&D, or industrial institutions. A list of at least five institutional clients (with contact information) must be provided as a reference.

It is mandatory that the bidder or OEM has a registered support office in India to provide warranty and after-sales support. In the case of imported equipment, either the OEM or their authorized seller must submit a certificate confirming the presence of such a service support facility in India.

The OEM must also submit a declaration confirming the availability of spare parts for the quoted products for a minimum of one year and authorize the bidder to participate in the tender.

5. Financial Criteria

Each bidder must have an average annual turnover of Rs.5 Crores or more over the last three financial years (FY 2022-23, 2023-24, 2024-25). The turnover must be supported by a CA certificate or audited financial statements.

Prices quoted must be inclusive of all taxes (GST, customs, etc.), transportation, packaging, insurance, unloading, installation, commissioning, and training charges. There shall be no extra claim under any circumstances after the finalization of the bid.

The quoted prices must be firm and fixed throughout the duration of the contract. No escalation in price will be allowed under any pretext.

6. Evaluation and Award of Contract

All bids will be evaluated on the basis of compliance with the technical specifications, completeness of submitted documentation, financial eligibility, and price competitiveness. The contract shall be awarded to the bidder whose offer is determined to be technically responsive and lowest in cost.

The purchaser reserves the absolute right to reject any or all bids without assigning any reason. The final decision on selection will be at the sole discretion of the purchaser and shall be binding on all parties.

7. Warranty and After-Sales Service

All equipment must carry a minimum onsite warranty of at least **three years** from the date of successful installation and commissioning. During this warranty period, the bidder shall repair or replace any defective items at no additional cost to the purchaser. All associated transportation, testing, and labor costs shall be borne by the bidder.

In case of any service delay or failure to resolve issues during the warranty period, the purchaser reserves the right to invoke penalties or reject future business from the vendor.

8. Payment Terms

Payment shall be released only after the successful supply, installation, and commissioning of the equipment. Final inspection and acceptance will be carried out by the purchaser's technical committee.

No payment shall be made for equipment that is received in damaged condition, is non-functional, or fails to meet the required specifications. The bidder must submit all necessary documentation (delivery challans, installation report, warranty documents, training certificate, invoice, etc.) to process the payment.

9. Other Conditions

No bidder shall be given preference based on category, class, or affiliation. The procurement may be extended to additional phases (e.g., Phase II) depending on availability of funds and institutional requirements.

Delayed delivery or installation may result in cancellation of order or imposition of penalties, as deemed fit by the purchaser. The scope of the supply and service must be entirely as per the BoQ and technical specifications. Bids with partial compliance or deviations shall not be entertained.

10. Submission Deadline and Contact Details


All quotations must be submitted on or before 22.09.2025 to the email ID principal@nandhaengg.org and hard copy to be sent to:

The principal,
Nandha Engineering College,
Erode – Perundurai main road,
Erode-638 052,
Tamil Nadu.


Contact: Dr. U. S. Ragupathy, Chief Mentor, AICTE IDEA Lab, Ph. No. 7373712234,

Dr. M. Easwaramoorthi, Coordinator, AICTE IDEA Lab, Ph. No.: 7373714707

Email: principal@nandhaengg.org


26/08/25




Dr. U. S. Ragupathy
Principal
Nandha Engineering College
(Autonomous)
Erode - 638 052, Tamil Nadu